



Main

| | |
|---------------------------|--|
| Range | Easy9 |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Provided equipment | 1 x washer 4 x screws Removable front cover Prefabricated flexible connection Insulated fishbone Adjustable pan assembly Provision for incomer |

Complementary

| | |
|--------------------------|---------------------|
| Enclosure mounting | Surface Flush |
| Number of plates | 6 for plain plate |
| Network number of phases | Three phase |
| Number of ways | 12 ways |
| Type of rail | DIN |
| Cable entry | 11 knock-outs |
| Type of door | Plain door |
| [In] rated current | 125 A |
| Enclosure material | Powder coated steel |
| Width | 470 mm outside: |
| Height | 526 mm outside: |
| Depth | 105 mm outside: |
| Colour | Grey (RAL 7035) |

Environment

| | |
|-----------|-------------|
| Standards | IEC 61439-1 |
|-----------|-------------|

IEC 61439-3

| | |
|---------------------------------------|--|
| Product certifications | ASTA |
| IP degree of protection | IP40 conforming to IEC 60529 (closed door) |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Ambient air temperature for operation | 50 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |



Main

| | |
|---------------------------|--|
| Range | Easy9 |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Provided equipment | 1 x washer 4 x screws Removable front cover Prefabricated flexible connection Insulated fishbone Adjustable pan assembly Provision for incomer |

Complementary

| | |
|--------------------------|---------------------|
| Enclosure mounting | Flush Surface |
| Number of plates | 6 for plain plate |
| Network number of phases | Three phase |
| Number of ways | 18 ways |
| Type of rail | DIN |
| Cable entry | 11 knock-outs |
| Type of door | Plain door |
| [In] rated current | 125 A |
| Enclosure material | Powder coated steel |
| Width | 470 mm outside: |
| Height | 580 mm outside: |
| Depth | 105 mm outside: |
| Colour | Grey (RAL 7035) |

Environment

| | |
|-----------|-------------|
| Standards | IEC 61439-3 |
|-----------|-------------|

IEC 61439-1

| | |
|---------------------------------------|--|
| Product certifications | ASTA |
| IP degree of protection | IP40 conforming to IEC 60529 (closed door) |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Ambient air temperature for operation | 50 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |



Main

| | |
|---------------------------|--|
| Range | Easy9 |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Provided equipment | 1 x washer 4 x screws Removable front cover Prefabricated flexible connection Insulated fishbone Adjustable pan assembly Provision for incomer |

Complementary

| | |
|--------------------------|---------------------|
| Enclosure mounting | Flush Surface |
| Number of plates | 6 for plain plate |
| Network number of phases | Three phase |
| Number of ways | 24 ways |
| Type of rail | DIN |
| Cable entry | 11 knock-outs |
| Type of door | Plain door |
| [In] rated current | 125 A |
| Enclosure material | Powder coated steel |
| Width | 470 mm outside: |
| Height | 633 mm outside: |
| Depth | 105 mm outside: |
| Colour | Grey (RAL 7035) |

Environment

| | |
|-----------|-------------|
| Standards | IEC 61439-3 |
|-----------|-------------|

IEC 61439-1

| | |
|---------------------------------------|--|
| Product certifications | ASTA |
| IP degree of protection | IP40 conforming to IEC 60529 (closed door) |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Ambient air temperature for operation | 50 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |



Main

| | |
|---------------------------|--|
| Range | Easy9 |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Provided equipment | 1 x washer 4 x screws Removable front cover Prefabricated flexible connection Insulated fishbone Adjustable pan assembly Provision for incomer |

Complementary

| | |
|--------------------------|---------------------|
| Enclosure mounting | Flush Surface |
| Number of plates | 6 for plain plate |
| Network number of phases | Three phase |
| Number of ways | 36 ways |
| Type of rail | DIN |
| Cable entry | 11 knock-outs |
| Type of door | Plain door |
| [In] rated current | 125 A |
| Enclosure material | Powder coated steel |
| Width | 470 mm outside: |
| Height | 740 mm outside: |
| Depth | 105 mm outside: |
| Colour | Grey (RAL 7035) |

Environment

| | |
|-----------|-------------|
| Standards | IEC 61439-1 |
|-----------|-------------|

IEC 61439-3

| | |
|---------------------------------------|--|
| Product certifications | ASTA |
| IP degree of protection | IP40 conforming to IEC 60529 (closed door) |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Ambient air temperature for operation | 50 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |



Main

| | |
|---------------------------|---|
| Range | Easy9 |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Provided equipment | 1 x washer Identification label 4 x screws Removable front cover |

Complementary

| | |
|--------------------------|---------------------|
| Enclosure mounting | Surface Flush |
| Nb of horizontal rows | 1 |
| Number of plates | 2 for plain plate |
| Network number of phases | Single phase |
| Number of ways | 6 ways |
| Type of rail | DIN |
| Cable entry | 4 knock-outs |
| Type of door | Plain door |
| [In] rated current | 100 A |
| Enclosure material | Powder coated steel |
| Width | 290 mm outside: |
| Height | 232 mm outside: |
| Depth | 90 mm outside: |
| Colour | Grey (RAL 7035) |

Environment

| | |
|-----------|----------------------------|
| Standards | IEC 61439-3 IEC 61439-1 |
|-----------|----------------------------|

| | |
|---------------------------------------|--|
| Product certifications | ASTA |
| IP degree of protection | IP40 conforming to IEC 60529 (closed door) |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Ambient air temperature for operation | 50 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |



Main

| | |
|---------------------------|---|
| Range | Easy9 |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Provided equipment | 1 x washer Identification label 4 x screws Removable front cover |

Complementary

| | |
|--------------------------|---------------------|
| Enclosure mounting | Surface Flush |
| Nb of horizontal rows | 1 |
| Number of plates | 3 for plain plate |
| Network number of phases | Single phase |
| Number of ways | 8 ways |
| Type of rail | DIN |
| Cable entry | 6 knock-outs |
| Type of door | Plain door |
| [In] rated current | 100 A |
| Enclosure material | Powder coated steel |
| Width | 362 mm outside: |
| Height | 232 mm outside: |
| Depth | 90 mm outside: |
| Colour | Grey (RAL 7035) |

Environment

| | |
|-----------|----------------------------|
| Standards | IEC 61439-1 IEC 61439-3 |
|-----------|----------------------------|

| | |
|---------------------------------------|--|
| Product certifications | ASTA |
| IP degree of protection | IP40 conforming to IEC 60529 (closed door) |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Ambient air temperature for operation | 50 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |



Main

| | |
|---------------------------|---|
| Range | Easy9 |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Provided equipment | 1 x washer Identification label 4 x screws Removable front cover |

Complementary

| | |
|--------------------------|---------------------|
| Enclosure mounting | Surface Flush |
| Nb of horizontal rows | 1 |
| Number of plates | 5 for plain plate |
| Network number of phases | Single phase |
| Number of ways | 12 ways |
| Type of rail | DIN |
| Cable entry | 8 knock-outs |
| Type of door | Plain door |
| [In] rated current | 100 A |
| Enclosure material | Powder coated steel |
| Width | 470 mm outside: |
| Height | 232 mm outside: |
| Depth | 90 mm outside: |
| Colour | Grey (RAL 7035) |

Environment

| | |
|-----------|----------------------------|
| Standards | IEC 61439-1 IEC 61439-3 |
|-----------|----------------------------|

| | |
|---------------------------------------|--|
| Product certifications | ASTA |
| IP degree of protection | IP40 conforming to IEC 60529 (closed door) |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Ambient air temperature for operation | 50 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |